

Description & Features:

- Excellent flow regulation and leak tight
- The one-piece body construction (no welding) provides strength, safety and corrosion resistance
- "Slow opening" prevents sudden pressure surge and instrument damage
- · Material includes stainless steel and stainless steel NACE
- Available in Hard Seat (6,000 and 10,000 psi)
- ASME B1.20.1 compliant
- CRN registered
- 1 year warranty

Applications:

 Ideally suited for severe duty oil and gas installations including refineries and processing plants as well as water treatment plants, power plants and hydraulic applications

Angle Body Order Codes (products in bold are normally stock in North America)

NPT Connection Material Max. Pressure Code 6,000 psi NVA8020 1/4" Female x 1/4" Female 10,000 psi NVA9020 NVA8000 1/4" Male x 6,000 psi 1/4" Female 10,000 psi NVA9000 3/8" Female x 6,000 psi NVA8024 3/8" Female 10,000 psi NVA9024 6,000 psi NVA8004 3/8" Male x 3/8" Female 10,000 psi NVA9004 6,000 psi NVA8021 1/2" Female x 1/2" Female 10,000 psi NVA9021 6,000 psi NVA8001 1/2" Male x 1/2" Female NVA9001 10,000 psi Stainless Steel 6,000 psi NVA8022 3/4" Female x 1/2" Female 10,000 psi NVA9022 6,000 psi NVA8002 3/4" Male x 1/2" Female NVA9002 10,000 psi 3/4" Female x 6,000 psi NVA8025 3/4" Female NVA9025 10,000 psi 6,000 psi NVA8005 3/4" Male x 3/4" Female 10,000 psi NVA9005 6,000 psi NVA8023 1" Female x 1" Female 10,000 psi NVA9023 1" Male x 6,000 psi NVA8003 1" Female 10,000 psi NVA9003

Angle Body NACE Order Codes

Aligie body NAOL Older Oddes							
NPT Connection	Material	Max. Pressure	Code				
1/4" Female x	Stainless Steel NACE	6,000 psi	NVA8020N				
1/4" Female		10,000 psi	NVA9020N				
1/4" Male x		6,000 psi	NVA8000N				
1/4" Female		10,000 psi	NVA9000N				
3/8" Female x		6,000 psi	NVA8024N				
3/8" Female		10,000 psi	NVA9024N				
3/8" Male x		6,000 psi	NVA8004N				
3/8" Female		10,000 psi	NVA9004N				
1/2" Female x		6,000 psi	NVA8021N				
1/2" Female		10,000 psi	NVA9021N				
1/2" Male x		6,000 psi	NVA8001N				
1/2" Female		10,000 psi	NVA9001N				
3/4" Female x		6,000 psi	NVA8022N				
1/2" Female		10,000 psi	NVA9022N				
3/4" Male x		6,000 psi	NVA8002N				
1/2" Female		10,000 psi	NVA9002N				
3/4" Female x		6,000 psi	NVA8025N				
3/4" Female		10,000 psi	NVA9025N				
3/4" Male x		6,000 psi	NVA8005N				
3/4" Female		10,000 psi	NVA9005N				
1" Female x		6,000 psi	NVA8023N				
1" Female		10,000 psi	NVA9023N				
1" Male x		6,000 psi	NVA8003N				
1" Female		10,000 psi	NVA9003N				

Option suffix:

CPM = Carbon steel panel mount kit


SPM = Stainless steel panel mount kit

Material


Description	Component Number	Stainless Steel	Stainless Steel NACE
Body	1	316 SS	316 SS NACE
Bonnet	2	316 SS	316 SS NACE
Adapter Locknut	3	304 SS	304 SS
Adapter	4	316 SS	316 SS NACE
Dustcap	5	Nylon	Nylon
Handle	6	304 SS	304 SS
Screw	7	304 SS	304 SS
Fastening Screw	8	304 SS	304 SS
Needle / Needle Tip	9	316 SS	316 SS NACE
Gland Washer	10	304 SS	304 SS
Gland Packing	11	Teflon® / Graphite	Teflon® / Graphite
Dwell Pin	12	304 SS	304 SS
Gland Packing	13	Teflon® / Graphite	Teflon® / Graphite

Female x Female

Male x Female



Panel Mont Kit (CPM/SPM)



Dimensions

Size	Н	L	SQ
1/4" Female x 1/4" Female	1.81" (46mm)	4.10" (104mm)	1.10" (28mm)
1/4" Male x 1/4" Female	1.77" (45mm)	4.02" (102mm)	1.10" (28mm)
3/8" Female x 3/8" Female	1.81" (46mm)	4.10" (104mm)	1.10" (28mm)
3/8" Male x 3/8" Female	1.77" (45mm)	4.02" (102mm)	1.10" (28mm)
1/2" Female x 1/2" Female	1.97" (50mm)	4.25" (108mm)	1.10" (28mm)
1/2" Male x 1/2" Female	1.97" (50mm)	4.25" (108mm)	1.10" (28mm)
3/4" Female x 1/2" Female	1.97" (50mm)	4.25" (108mm)	1.26" (32mm)
3/4" Male x 1/2" Female	1.97" (50mm)	4.25" (108mm)	1.10" (28mm)
3/4" Female x 3/4" Female	1.97" (50mm)	4.25" (108mm)	1.26" (32mm)
3/4" Male x 3/4" Female	1.97" (50mm)	4.25" (108mm)	1.26" (32mm)
1" Female x 1" Female	2.48" (63mm)	4.84" (123mm)	1.58" (40mm)
1" Male x 1" Female	2.48" (63mm)	4.84" (123mm)	1.58" (40mm)

Teflon® is a registered trademark of DuPont Corporation