## **Hydrostatic Pressure Level Switch**



measuring

monitoring

analyzing

**NLP** 



- Suitable for a Wide Variety of Media
- No Moving Parts and Minimal Maintenance
- No External Power Required
- Process Connection: 1" NPT, G1
- Max. Process Temp: 158 °F
- Switching Range up to 16 ft
- Switch Rating: 250 VAC, 1A



KOBOLD companies worldwide:

ARGENTINA, AUSTRALIA, AUSTRIA, BELGIUM, BULGARIA, CANADA, CHILE, CHINA, COLOMBIA, CZECH REPUBLIC, EGYPT, FRANCE, GERMANY, HUNGARY, INDIA, INDONESIA, ITALY, MALAYSIA, MEXICO, NETHERLANDS, PERU, POLAND, REPUBLIC OF KOREA, ROMANIA, SINGAPORE, SPAIN, SWITZERLAND, TAIWAN, THAILAND, TUNISIA, TURKEY, UNITED KINGDOM, USA, VIETNAM

KOBOLD Instruments, Inc. 1801 Parkway View Drive Pittsburgh, PA 15205

Main Office:

www.koboldusa.com

1.800.998.1020 1.412.788.4890 info@koboldusa.com





## **Description**

The KOBOLD NLP Hydrostatic Pressure Level Switch excels in level control in open tanks where suspended deposits are present. Operation of the switch is based upon the change in hydrostatic pressure within the standpipe. When the media rises or falls to the desired level, the changing air pressure within the tube reacts on the internal diaphragm, actuating or de-actuating the SPDT contact within the switch housing. The switchpoint can easily be adjusted in the field by turning a screw located within the switch housing.

## **Features**

- Suitable for a wide variety of free-flowing liquids in open tanks
- No moving parts
- Polypropylene or PVDF wetted parts
- No external power required
- Minimal maintenance required

## **Technical Details**

Process Connection:1" NPT, G1Max. Process Temp:158 °FSwitch Rating:250 VAC, 1A

Fitting/Tube Material: Polypropylene or PVDF

Protection: IP65

Stand-pipe Length: 3 ft, 6 ft, 10 ft, or custom up to 16 ft

Cable Gland: M20

| Ordering Details |                     |        |   |               |                       |   |
|------------------|---------------------|--------|---|---------------|-----------------------|---|
| NI               | NLP- = Level Switch |        |   |               |                       |   |
|                  |                     | P<br>T |   | = Po<br>= PV  | lypropy<br>DF         | ylene <b>Material</b>   |
|                  |                     |        |   | R<br>N<br>X   | = G1<br>= 1"<br>= cus |   |
|                  |                     |        | • |               | 0<br>1<br>2<br>3<br>X | = tubeless, internal G 3/8 thread Measuring Tube = 3 ft = 6 ft = 10 ft = custom (please specify length) |
| N                | ∳<br>LP-            | ∳<br>P |   | <b>↓</b><br>N | 1                     | Example NLP Order Code  |



