

Description & Features:

- Combines isolating and venting in a single valve, eliminating the need for tubing and fittings
- Block valve isolates the downstream process fluids, and the bleed valve exhausts upstream fluids enabling instruments to be removed without disturbing the permanent piping installation on the bottom
- The 1/4" NPT vent plug is located 90° to the left and may be removed and replaced with exhaust piping to direct the fluids to a safe location
- Available in Hard Seat (10,000 psi)
- All stems are 316 stainless steel
- CRN pending
- 1 year warranty

Applications:

 Ideally suited for severe duty oil and gas installations including refineries and processing plants as well as water treatment plants, power plants and hydraulic applications where additional safety for shut-down and media venting is required

Double Block & Bleed Order Codes

NPT Connection	Material	Seat	Max. Pressure	Code	
1/4" Female x 1/4" Female	Stainless			BBV3420	
1/4" Male x 1/4" Female		/4" Female Stainless	Hard Coat	10 000 pg	BBV3400
1/2" Female x 1/2" Female		Hard Seat	10,000 psi	BBV3421	
1/2" Male x 1/2" Female				BBV3401	

Double Block & Bleed NACE Order Codes

NPT Connection	Material	Seat	Max. Pressure	Code		
1/4" Female x 1/4" Female	Stainless Steel NACE			BBV3420N		
1/4" Male x 1/4" Female			nale The last	Hard Coat	10.000 psi	BBV3400N
1/2" Female x 1/2" Female		Hard Seat	10,000 psi	BBV3421N		
1/2" Male x 1/2" Female				BBV3401N		

Replacement Bleed Screw and Plug Order Codes

Plug or Screw	Stainless Steel	Stainless Steel NACE	
M8 Bleed Screw	NVAPLUG01	NVAPLUG01N	
1/4" NPT Plug	NVAPLUG03	NVAPLUG03N	

Material

Description	Component Number	Stainless Steel	Stainless Steel NACE	
Body	1	316 SS	316 SS NACE	
Bonnet	2	316 SS	316 SS NACE	
Dust Cap	3	Nylon	Nylon	
Needle / Needle Tip	4	316 SS	316 SS NACE	
Handle	5	304 SS	304 SS	
Screw	6	304 SS	304 SS	
Fastening Screw	7	304 SS	304 SS	
O-Rings	8	FKM	FKM	
Gland Packing	9	Teflon®	Teflon®	
Dwell Pin	10	304 SS	304 SS	
Vent Plug	11	316 SS	316 SS NACE	


Dimensions


Size	Н	L	SQ	SQ1	M	N	Р
1/4" Female x 1/4" Female	3.70" (94mm)	3.54" (90mm)	1.57" (40mm)	1.75" (44.5mm)	5.20" (132mm)	1.97" (50mm)	1.50" (38mm)
1/4" Male x 1/4" Female	4.02" (102mm)	3.54" (90mm)	1.57" (40mm)	1.75" (44.5mm)	5.20" (132mm)	1.97" (50mm)	1.50" (38mm)
1/2" Female x 1/2" Female	3.70" (94mm)	3.54" (90mm)	1.57" (40mm)	1.75" (44.5mm)	5.20" (132mm)	1.97" (50mm)	1.50" (38mm)
1/2" Male x 1/2" Female	4.02" (102mm)	3.54" (90mm)	1.57" (40mm)	1.75" (44.5mm)	5.20" (132mm)	1.97" (50mm)	1.50" (38mm)


Female x Female

Block Valve Block Valve Block Valve

Male x Female







Teflon® is a registered trademark of DuPont Corporation